

Dimpled Ceramic Lagging

PRODUCT
FACT
SHEET

The range of TS Global ceramic pulley lagging has been engineered to provide an accentuated positive drive between pulley and belt, especially in conditions that normal rubber lagging would not accommodate.

Our dimpled ceramic lagging excels in challenging environments and offers improved defence against wear, thus reducing maintenance.

Balancing cost effectiveness with long life functionality makes this the ideal choice for your application.



Application

All conveyor drive pulleys.

-  Proven Performance
-  Quality Product
-  Flexibility in Design
-  On-time Delivery

FEATURES	BENEFITS
Manufactured with CN bonding layer	= Delivers rubber tear bond to the shell which increases longevity
Manufactured with 92% aluminium oxide tiles	= Extreme wear resistance of lagging
	= Reduces maintenance
	= Reduces hazards associated with re-lagging the pulley
Manufactured with raised dimples	= Increases drive efficiency and improves belt grip
Ceramic tiles bonded to rubber on all edges	= Superior bond and tile pull-out (rubber tear)
Factory buffed back and edges	= Eliminates hazards associated with buffing
	= Reduces installation time and cost
Manufactured to suit specific belt widths	= Reduces wastage
Can be installed in-situ without having to remove the pulley	= Eliminates hazards associated with removing pulley
	= Reduced costs associated with removing pulley and crane hire
Manufactured with cutting sypes	= Allows easy adjustment of strip width to pulley diameter
Lagging packed in plastic film	= Eliminates contamination of the buffed bonding layer

*Available in natural (SBR) and fire resistant anti-static (FRAS) compounds

Dimpled Ceramic Lagging

PRODUCT
FACT
SHEET



Item Code Natural Rubber	Item Code FRAS Rubber	Description	Unit	Strip Length		Ceramic Width		Thickness		Weight	
				(mm)	(inches)	(mm)	(inches)	(mm)	(inches)	(kg)	(lbs)
29-12-001	29-13-001	Lagging Ceramic Dimpled 0650mm	Strip	1050	41 5/16	650	25 5/16	12	1/2	5	10
29-12-002	29-13-002	Lagging Ceramic Dimpled 0700mm	Strip	1100	43 5/16	700	27 5/16	12	1/2	5	11
29-12-003	29-13-003	Lagging Ceramic Dimpled 0800mm	Strip	1200	47 1/4	800	31 1/2	12	1/2	6	12
29-12-004	29-13-004	Lagging Ceramic Dimpled 0900mm	Strip	1300	51 3/16	900	35 7/16	12	1/2	6	13
29-12-005	29-13-005	Lagging Ceramic Dimpled 0950mm	Strip	1350	53 1/8	950	37 3/8	12	1/2	6	14
29-12-006	29-13-006	Lagging Ceramic Dimpled 1050mm	Strip	1450	57 1/16	1050	41 5/16	12	1/2	7	15
29-12-031	29-13-031	Lagging Ceramic Dimpled 1100mm	Strip	1500	59 1/16	1100	43 3/16	12	1/2	7	16
29-12-007	29-13-007	Lagging Ceramic Dimpled 1200mm	Strip	1600	63	1200	47 1/4	12	1/2	8	17
29-12-032	29-13-032	Lagging Ceramic Dimpled 1300mm	Strip	1700	66 15/16	1300	51 5/16	12	1/2	8	18
29-12-008	29-13-008	Lagging Ceramic Dimpled 1400mm	Strip	1800	70 7/8	1400	55 1/8	12	1/2	9	19
29-12-009	29-13-009	Lagging Ceramic Dimpled 1500mm	Strip	1900	74 13/16	1500	59 1/16	12	1/2	9	20
29-12-010	29-13-010	Lagging Ceramic Dimpled 1600mm	Strip	2000	78 3/4	1600	63	12	1/2	10	22
29-12-034	29-13-033	Lagging Ceramic Dimpled 1700mm	Strip	2100	82 11/16	1700	66 15/16	12	1/2	10	23
29-12-011	29-13-011	Lagging Ceramic Dimpled 1800mm	Strip	2200	86 3/8	1800	70 7/8	12	1/2	11	24
29-12-012	29-13-012	Lagging Ceramic Dimpled 1900mm	Strip	2300	90 9/16	1900	74 13/16	12	1/2	11	25
29-12-013	29-13-013	Lagging Ceramic Dimpled 2100mm	Strip	2500	98 7/16	2100	82 11/16	12	1/2	13	28
29-12-014	29-13-014	Lagging Ceramic Dimpled 2200mm	Strip	2600	102 3/8	2200	86 3/8	12	1/2	13	29
29-12-015	29-13-015	Lagging Ceramic Dimpled 2300mm	Strip	2700	106 5/16	2300	90 9/16	12	1/2	14	30
29-12-016	29-13-016	Lagging Ceramic Dimpled 2400mm	Strip	2800	110 1/4	2400	94 1/2	12	1/2	14	31
29-12-017	29-13-017	Lagging Ceramic Dimpled 2500mm	Strip	2900	114 3/16	2500	98 7/16	12	1/2	15	32
29-12-018	29-13-018	Lagging Ceramic Dimpled 2600mm	Strip	3000	118 1/8	2600	102 3/8	12	1/2	15	34
29-12-019	29-13-019	Lagging Ceramic Dimpled 2700mm	Strip	3100	122 1/16	2700	106 5/16	12	1/2	16	35
29-12-020	29-13-020	Lagging Ceramic Dimpled 2800mm	Strip	3200	126	2800	110 1/4	12	1/2	16	36
29-12-021	29-13-021	Lagging Ceramic Dimpled 2900mm	Strip	3300	129 15/16	2900	114 3/16	12	1/2	17	37
29-12-022	29-13-022	Lagging Ceramic Dimpled 3000mm	Strip	3400	133 3/8	3000	118 1/8	12	1/2	17	38

For more information, please contact TS Global directly and/or your TS Global product distributor.

DISTRIBUTED BY

PHONE 1300 418 298 • **EMAIL** sales@tsglobal.net.au • **WEB** www.tsglobal.net.au

WELSHPOOL WA • TOMAGO NSW • MACKAY QLD

ABN 30 603 644 748

