

Redi Repair Product Range

PRODUCT
FACT
SHEET



Redi Repair provides a simple, efficient and cost effective solution for a damaged or torn conveyor belt. It delivers a fast curing, high quality bond to the belt surface. The two-part 100% solids polyurethane material also provides excellent abrasion and tear resistance. Our Redi Repair accessories have been developed to assist in safe and efficient application of the product by avoiding air entrapment, improving product mixing consistency, minimising waste and increasing productivity



Application

Suitable for repairs to rubber (fabric and steel cord) and PVC (solid woven) conveyor belts, including repairing tears, spot/punctures, holes, skirt damage, edge damage, splice damage and protecting mechanical fasteners.

Properties

Colour:	Red	Hardness:	80 - 85A
Shrinkage:	<1%	Shelf life:	12 months @ 22°C (71.6°F)
Working time:	10 to 15 mins @ 24°C (75.2°F)	Return belt to service:	4 hr @ 24°C (75.2°F)

- Proven Performance
- Quality Product
- Flexibility in Design

FEATURES	BENEFITS
Fast curing (30 minutes)	= Minimises downtime for maintenance = Increases conveyor availability
Working time of 10-15 minutes	= Increases time for applicators to apply product
High viscosity	= Able to be applied on inclines up to 45 degrees without sagging or slumping
High quality bond	= Increases longevity of the repair over traditional techniques
Excellent abrasion and tear resistance	= Increases life in high wear zones = Increases strength throughout the repair
Light and compact	= Reduces hazards associated with manual handling of capital equipment such as vulcanisers and spot presses
Self-mixing	= Product is automatically mixed to correct ratio via self-mixing nozzle eliminating human error = No-hand mixing required
Cost efficient	= Minimal labour to apply = No hire charge for equipment = Long lasting

PHONE 1300 418 298 • **EMAIL** sales@tsglobal.net.au • **WEB** www.tsglobal.net.au

WELSHPOOL WA • **TOMAGO NSW** • **MACKAY QLD**

ABN 30 603 644 748



Redi Repair Product Range

PRODUCT
FACT
SHEET



Repair Materials

Item Code	Description	Unit	Weight		Volume	
			(g)	(oz)	(ml)	(Fl oz)
60-13-100	Redi Repair Natural 85 kit (including 1 x Redi Repair Natural 85, Cleaning Solution N85, Primer N85, mixing nozzle, paint brush, plastic scraper, rubber gloves).	Each	1100	39	1000	34

For more information, please contact TS Global directly and/or your TS Global product distributor.

Accessories

Item Code	Description	Unit	Weight	
			(kg)	(lbs)
60-13-168	Battery caulking gun kit with 2.0Ah battery and charger	Each	7	14
60-13-169	Battery caulking gun kit (skin only)	Each	6	12
60-13-170	Pneumatic caulking gun	Each	2	3.0
60-13-171	Manual caulking gun	Each	0.6	1.0
60-13-172	Static mixing nozzle	Each	0.1	0.2
60-13-173	250mm (10") Steel scraper	Each	0.1	0.2
60-13-174	150mm (6") Plastic scraper	Each	0.1	0.2
60-13-175	Paint Brush	Each	0.1	0.2

For more information, please contact TS Global directly and/or your TS Global product distributor.



DISTRIBUTED BY

PHONE 1300 418 298 • **EMAIL** sales@tsglobal.net.au • **WEB** www.tsglobal.net.au
WELSHPOOL WA • **TOMAGO NSW** • **MACKAY QLD**

ABN 30 603 644 748

