

# Roller Carrier

PRODUCT  
FACT  
SHEET

The TS Global Roller Carrier has been designed to minimise safety hazards associated with carrying conveyor rollers along the conveyor. The use of the roller carrier ensures that the worker has a hand free to maintain 3 points of contact on stairs or gantries. The unit is designed to accept 14 and 22mm Across the Flat (A/F) rollers and can be used by an individual or as part of a 2-person lift.

Balancing cost effectiveness with long life functionality makes this the ideal choice for your application.

## Application

Used on all Flat Return, Vee Return and Trough rollers under 50kg with either 14 or 22mm A/F slots as an individual or up to 100kg as part of a 2 person lift.



-  Proven Performance
-  Quality Product
-  Flexibility in Design
-  On-time Delivery

FEATURES	BENEFITS
Manufactured from 304 stainless steel	= Eliminates corrosion and maximises life
Supplied with a padded and adjustable shoulder strap	= Allows the worker to carry the roller, leaving hands free
	= Minimises safety hazards
	= Can be adjusted to suit the worker
	= Improved comfort
Can be used for a dual lift on longer and heavier rollers	= Minimises manual handling hazards on heavy or long rollers
Designed with SWL of 50kgs	= Certified SWL eliminates the risk of component failure under normal use
Designed with a safety clasp	= Ensures that roller is safely retained within the Roller Carrier and cannot dislodge