

# Soft 40 Skirting Rubber

**Soft 40 Skirting Rubber is a highly flexible wear resistant 40 Duro rubber designed for use as a conveyor sealing skirt.**

## FEATURES

Soft 40 Skirting Rubber is made from a highly elastic premium grade rubber compound and will display excellent resistance to abrasion.

Soft 40 Skirting Rubber has excellent physical properties including mechanical strength and tear resistance.

Soft 40 Skirting is highly flexible and is designed to bend against the conveyor belt to create a seal once adjusted. This flexible seal reduces both material spillage and dust escaping even on systems with inconsistent belt levels. This design pro-longs the life of the skirt and also minimizes the potential of wear and damage to the conveyor belt itself.

Soft 40 Skirting Rubber can be supplied in full rolls or pre-cut skirting rubber strips to suit standard conveyor system designs, ready for easy installation.



## TECHNICAL INFORMATION

Polymer	NR	
Colour	Black	
Specific Gravity	1.12	ASTM D297
Hardness	40° ± 5° Shore A	ASTM D2240
Tensile Strength	18 MPa (min)	ASTM D412
Elongation @ Break	550% (min)	ASTM D412
Abrasion	100mm <sup>3</sup> (max) @5N	ASTM D5963
Temperature Range	-20°C to +70°C	
Tear Strength	60 N/mm (min)	ASTM D624

## AVAILABLE SIZES

Soft 40 Skirting Rubber in a range of standard thicknesses and roll sizes. It can also be supplied in cut lengths, strips, pads and a wide variety of custom cut shapes to suit your application requirement.

SIZE	WEIGHT (PER L/M)
3mm x 1500mm (10 L/M Rolls)	5.2 kgs
6mm x 1500mm (30 L/M Rolls)	10.4 kgs
9mm x 1500mm (30 L/M Rolls)	15.6 kgs
12mm x 1500mm (30 L/M Rolls)	20.7 kgs
16mm x 1500mm (30 L/M Rolls)	27.6 kgs
19mm x 1500mm (30 L/M Rolls)	32.8 kgs
25mm x 1500mm (10 L/M Rolls)	43.2 kgs

## AVAILABLE STRIPS

Soft 40 Skirting Rubber is also stocked in a variety of pre-cut strips 6mm to 25mm thick in widths 75mm, 100mm, 125mm, 150mm, 200mm, 250mm and 300mm. It can also be supplied in custom widths or with a 45 degree bevel.